

## Articulating Cranes

IMT articulating cranes provide superior lift-to-weight ratios, outstanding quality, and proven reliability and performance.

Model	Crane Rating	Max Horizontal Reach	Max Vertical Reach*	Max Lift Capacity	Crane Weight
2.5/18	18,085 ft-lb (2.5 tm)	18' 4" (5.6 m)	23' 10" (7.3 m)	1740 lb (790 kg)	850 lb (386 kg)
3.2/23	23,145 ft-lb (3.2 tm)	14' 5" (4.4 m)	20' 2" (6.2 m)	2195 lb (995 kg)	920 lb (418 kg)
5/33	32,550 ft-lb (4.5 tm)	16' 1" (4.9 m)	23' (7 m)	2975 lb (1350 kg)	1255 lb (569 kg)
6/39	39,060 ft-lb (5.4 tm)	17' 1" (5.2 m)	23' 4" (7.1 m)	3525 lb (1600 kg)	1630 lb (740 kg)
7/48	48,460 ft-lb (6.7 tm)	17' 1" (5.2 m)	23' 7" (7.2 m)	4300 lb (1950 kg)	1905 lb (865 kg)
9/65SL	65,100 ft-lb (9 tm)	18' (5.5 m)	25' 7" (7.8 m)	8380 lb (3800 kg)	2360 lb (930 kg)
9/65DL	63,650 ft-lb (8.8 tm)	18' (5.5 m)	25' 7" (7.8 m)	9040 lb (4100 kg)	2415 lb (1094 kg)
10/72SL	72,330 ft-lb (10 tm)	18' (5.5 m)	25' 7" (7.8 m)	9280 lb (4210 kg)	2380 lb (1080 kg)
10/72DL	70,160 ft-lb (9.7 tm)	18' (5.5 m)	25' 7" (7.8 m)	9945 lb (4510 kg)	2380 lb (1080 kg)
11/78SL	77,395 ft-lb (10.7 tm)	20' (6.1 m)	27' 5" (8.4 m)	9170 lb (4160 kg)	2570 lb (1165 kg)
11/78DL	76,670 ft-lb (10.6 tm)	20' (6.1 m)	27' 5" (8.4 m)	9280 lb (4210 kg)	2570 lb (1165 kg)
12/86SL	86,075 ft-lb (11.9 tm)	20' (6.1 m)	27' 5" (8.3 m)	10,165 lb (4610 kg)	2590 lb (1175 kg)
12/86DL	84,625 ft-lb (11.7 tm)	20' (6.1 m)	27' 5" (8.3 m)	10,230 lb (4640 kg)	2665 lb (1210 kg)
13/86SL	88,245 ft-lb (12.2 tm)	20' 4" (6.2 m)	28' 7" (8.7 m)	9920 lb (4500 kg)	2890 lb (1310 kg)
13/88DL	87,520 ft-lb (12.1 tm)	20' 4" (6.2 m)	28' 7" (8.7 m)	10,780 lb (4890 kg)	3000 lb (1360 kg)
14/98SL	97,645 ft-lb (13.5 tm)	20' 4" (6.2 m)	28' 7" (8.7 m)	11,025 lb (5000 kg)	2890 lb (1310 kg)
14/98DL	97,645 ft-lb (13.5 tm)	20' 4" (6.2 m)	28' 7" (8.7 m)	11,885 lb (5390 kg)	3000 lb (1,360 kg)
15/105SL	104,880 ft-lb (14.5 tm)	20' 4" (6.2 m)	28' 7" (8.7 m)	12,125 lb (550 kg)	3020 lb (1370 kg)
15/105DL	104,880 ft-lb (14.5 tm)	20' 4" (6.2 m)	28' 7" (8.7 m)	13,470 lb (6110 kg)	3130 lb (1420 kg)
17/117SL	116,450 ft-lb (16.1 tm)	20' 4" (6.2 m)	28' 6" (8.7 m)	12,785 lb (5800 kg)	3020 lb (1370 kg)
17/117DL	115,730 ft-lb (16 tm)	20' 4" (6.2 m)	28' 6" (8.7 m)	14,835 lb (6730 kg)	3130 lb (1420 kg)
18/124SL	119,345 ft-lb (16.5 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	13,800 lb (6260 kg)	3900 lb (1770 kg)
18/124DL	120,070 ft-lb (16.6 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	14,265 lb (6470 kg)	4055 lb (1840 kg)
20/138SL	133,085 ft-lb (18.4 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	15,345 lb (6060 kg)	3900 lb (1770 kg)
20/138DL	133,085 ft-lb (18.4 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	15,740 lb (7140 kg)	4055 lb (1840 kg)
22/153SL	148,275 ft-lb (20.5 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	17,065 lb (7740 kg)	4180 lb (1895 kg)
22/153DL	149,000 ft-lb (20.6 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	17,550 lb (7960 kg)	4365 lb (1980 kg)
24/169SL	164,910 ft-lb (22.8 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	18,940 lb (8590 kg)	4180 lb (1895 kg)
24/169DL	165,635 ft-lb (22.9 tm)	27' 3" (8.3 m)	35' 1" (10.7 m)	19,355 lb (8780 kg)	4365 lb (1980 kg)
32/222	222,054 ft-lb (30.7 tm)	26' 9" (8.1 m)	35' 5" (10.8 m)	15,101 lb (6850 kg)	6085 lb (2760 kg)
40/275	274,855 ft-lb (38 tm)	26' 3" (8 m)	35' 4" (10.8 m)	19,025 lb (8630 kg)	7165 lb (3250 kg)
50/345	345,015 ft-lb (47.7 tm)	26' 11" (8.2 m)	35' 4" (10.8 m)	22,840 lb (10,360 kg)	8180 lb (3710 kg)
60/427	409,390 ft-lb (56.6 tm)	27' 3" (8.3 m)	36' 5" (11.1 m)	27,845 lb (12,630 kg)	9735 lb (4415 kg)
80/565	516,440 ft-lb (71.4 tm)	27' 3" (8.3 m)	36' 5" (11.1 m)	35,410 lb (16,060 kg)	12,345 lb (5600 kg)